



Art. Nr.: 11-6205 XKBU 812



Primary Current:	600
Secondary Current:	5
Burden (VA):	5
Accuracy Class:	1

Dimensions:

Bus bar 1 in mm:	80x120
Width in mm:	155
Height in mm:	198
Depth in mm:	58




Technical Data:

Therm. nominal continuous current I_{cth} : 1 x I_{pr}
 Therm. nominal short-time current I_{th} : 60 x I_{pr} , 1 Sek.
 Max. operating voltage U_m : 0,72 kV
 Isolation test voltage: 3 kV, U_{eff} , 50 Hz, 1 min
 Nominal rated frequency: 50/60 Hz
 Isolation class: E
 Accuracy classes of the harmonic measurements:
 Measurement accuracy up to 20 kHz:
 $\Delta\phi \leq 1^\circ$ @ 0,05-20 kHz
 $\varepsilon \leq 2\%$ @ 0,05-10 kHz
 $\varepsilon \leq 3\%$ @ 10-20 kHz

General Technical Data:

Over-current limiting factor:	See rating plate
Working temperature range:	$-5^\circ\text{C} < T < +50^\circ\text{C}$
Storage temperature range:	$-25^\circ\text{C} < T < +70^\circ\text{C}$
Unbreakable plastic housing made of grey polyamide:	Flame resistant, ultrasonically welded
Nickel-plated secondary terminals with plus-minus nickel-plated screws	M5x10mm
Custom tariff number	85043129
Applied standards 1	DIN EN 61869-1/2
Applied standards 2	DIN EN 42600-1/2

Technical Drawing:



Contact:

MBS AG & Co. KG - Eisbachstrasse 51 - D-74429 Sulzbach-Laufen - www.mbs-ag.com
 Tel.: +49 7976 9851-0 - Telefax: +49 7976 9851-90 - verkauf@mbs-ag.com

Date: 24.05.2025
