

Art. Nr.: CTB 61.35 CTB 61.35



Dimensions:

Bus bar 1 in mm:	63x10
Bus bar 2 in mm:	50x30
Round conductor in mm:	44
Width in mm:	95
Height in mm:	115
Depth in mm:	52

Technical Data:


Therm. nominal continuous current I_{cth} : $1,2 \times I_{pr}$
 Therm. nominal short-time current I_{th} : $60 \times I_{pr}$, 1 Sek.,
 max 100 kA
 Max. operating voltage U_m : 1,2 kV
 Isolation test voltage: 6 kV, U_{eff} , 50 Hz, 1 Min.
 Nominal rated frequency: 50 Hz
 Isolation class: B

General Technical Data:

Over-current limiting factor:
 Working temperature range:
 Storage temperature range:
 Custom tariff number
 Applied standards 1
 Applied standards 2
 UL certificated:

See rating plate
 $-5^{\circ}\text{C} < T < +50^{\circ}\text{C}$
 $-25^{\circ}\text{C} < T < +70^{\circ}\text{C}$
 85043129
 DIN EN 61869-1/2
 DIN EN 42600-1/2
 Certificate Number - 20100426-E336996

Technical Drawing:



Contact:

MBS AG - Eisbachstrasse 51 - D-74429 Sulzbach-Laufen - www.mbs-ag.com
 Tel.: +49 7976 9851-0 - Telefax: +49 7976 9851-90 - verkauf@mbs-ag.com

Date: 04.05.2024